

SIROMER TRACTORS EURO "E" SPECIFICATIONS

		204E	244E	354E			
OVERALL DIMENSIONS	L	3185 mm	3185 mm	3352 mm			
	W	1440-1460 mm	1440-1460 mm	1485-1785 mm			
	H	2530 mm	2530 mm	2420 mm			
WHEEL BASE(mm)		1645	1645	1833.5 mm			
TYRES (Agricultural)		front 6.00-12, rear 8.3-24	front 6.00-12, rear 8.3-24	front 7.5-16, rear 11.2-24			
TYRES (Agricultural option)		front 6.00-12, rear 12.5-18	front 6.00-12, rear 12.5-18	n/a			
TYRES (Turf)		front 7.50-12, rear 11.2-20	front 7.50-12, rear 11.2-20	front 9.50-16, rear 13-20			
PTO SPEED		540 / 1000 rpm	540 / 1000 rpm	540 / 1000 rpm			
CLUTCH		DUAL STAGE	DUAL STAGE	DUAL STAGE			
SPEED (Km/h)	FORWARD	NORMAL	CREEP	NORMAL	CREEP	NORMAL	CREEP
		1.64	0.3	1.73	0.32	2.25	1.79
		3.24	0.6	3.42	0.64	3	2.27
		5.41	1.01	5.7	1.05	4.22	3.69
		7.59	1.41	7.99	1.4	6.26	5.85
		15	2.79	15.79	2.94	10.37	7.63
		25	4.66	26.35	4.9	13.88	9.64
						19.45	15.96
					28.86	24.89	
	REVERSE	1.3	0.24	1.37	0.26	1.84	1.67
	6.02	1.12	6.34	1.18	7.12	6.47	
ENGINE	TYPE OF ENGINE	3 CYLINDER VERTICAL ,WATER COOLED 4 STROKE, INDIRECT INJECTION DIESEL	3 CYLINDER VERTICAL ,WATER COOLED 4 STROKE, INDIRECT INJECTION DIESEL	4 CYLINDER VERTICAL ,WATER COOLED 4 STROKE, DIESEL			
	RATED POWER	14.7 KW, 20 HP	17.6 KW ,24 HP	25.7 KW, 35 HP			
	RATED SPEED	2350 rpm	2350 rpm	2350 rpm			