

JINMA 45 HP 4WD TRACTOR SPECIFICATIONS

Pacific Supply Group Pty Ltd
ABN 12 116 215 304

Contact Steve 0422 345 146

Engine	Vertical, Water Cooled 4 Stroke Diesel, 3.039 L
Number of Cylinders	3
Engine Power	45 Hp 33.1 Kw
Rated power & Speed	33.1 kw 2200 r/min
Cold Start	Pre Heat
Electrical System	Single-Line System, negative Strap
Starting Engine	QD142 14V 2.5 Kw
Lights	Front, Rear, Brake, Indicator, Reverse/Working Electric
Horn	Oil pressure, Engine Temperature
Gauges/Indicators	Ammeter, rev Counter, Fuel Gauge
Braking System	Air Cushion Brake Valve Type ZDF-001
Clutch	10 inch, Dual Acting, Dry Friction
Drive Train	4 Wheel Drive Engage/Disengage
Steering	Hydraulic Ram, Power Assisted
Differential Lock	Selectable Engage/Disengage
1st Forward	2.188/0.328 Km/Hr
2nd Forward	3.215/0.481 Km/hr
3rd Forward	5.227/0.782 Km/Hr
4th Forward	6.863/1.027 Km/Hr
5th Forward	9.827/1.471 Km/Hr
6th Forward	14.437/2.161 Km/Hr
7th Forward	23.462/3.512 Km/Hr
8th Forward	30.815/4.613 Km/Hr
Reverse 1st	3.247/0.444 Km/Hr
Reverse 2nd	4.771/0.652 Km/Hr
Reverse 3rd	7.756/1.059 Km/Hr
Reverse 4th	10.181/1.391 Km/Hr
PTO	Semi Independent 2 Speed
High	1,000 rpm
Low	540 rpm
3 Point Linkage	Category 1, 2
Fuel Tank	35 Litres
Engine Oil Sump	6 Litres
Hydraulic Lifter	12 Litres
Dimensions and Weight	
Assembled	3.825m L x 1.625m W x 2.065m H / 1952 kgs